

REFLECTIVE LUTS V6.1.14.6 (Terra) / V6.1.17.8 (Aqua)

LUT NAME	DESCRIPTION	DIMENSIONS					Total Number of Elements	Terra (T) or Aqua (A) Only	TIME DEPENDENT LUTS ONLY				
		B	D	S	M	Other			# of Table Pieces	TERRA	AQUA	V6.1.14.6	V6.1.17.8
B26_B5_Corr_Switch	Flag to turn on (1) or off (0) the Band 26 correction	1	1	1	1	1	1		1	Step Function LUT			
B26_B5_Corr	Correction coefficients for the Band 26 correction	1	10	1	1	1	10		3	1	Step Function LUT		
B26_B5_Frame_Offset	Frame offset to use for the Band 26 correction	1	10	1	1	1	10						
DN_obi_avg_first_frame_to_use	Index of 1st frame to use when computing average OBC DN.	1	1	1	1	1	1						
DN_obi_avg_number_of_frames_to_use	Number of frames to use to compute average OBC DN.	1	1	1	1	1	1						
dn_sat_ev	Value of EV pixel dn to treat as saturated				1340*	1340*			11	8	Step Function LUT		
dn_star_Max	Maximum dn** value for scaling to the product scaled integer	22	1	1	1	1	22						
dn_star_Min	Minimum dn** value for scaling to the product scaled integer	22	1	1	1	1	22						
E_sun_over_pi	RSR-weighted solar irradiance/ pi for RSB detectors	1	330	1	1	1	330						
K_FPA	Focal Plane Array Temperature Correction Factor				1340*	1340*							
K_inst	Instrument Temperature Correction Factor				1340*	1340*			3	1	Step Function LUT		
m0	Reflectance Calibration offset				1340*	1340*							
m1	Reflectance Calibration linear terms				1340*	1340*			370	194	Piecewise Linear LUT		
RSB_specified_uncertainty	Factor used in computing uncertainty index	22	1	1	1	1	22						
RSB_SV_DN_moon_include_frames	Number of frames after sorting if moon in SVP	1	1	1	1	1	1						
RSB_UI_scaling_factor	Factor used in computing uncertainty index	22	1	1	1	1	22						
RVS_RefSB	Quadratic coefficients for calculating the EV RVS for RSB	22	40	1	2	5	8800		86	104	Piecewise Linear LUT		
Serial Number of Reflective LUT	Version number of reflective calibration LUTs	1	1	1	1	1	1						
SWIR_OOB_correction_switch	Flag which turns on (1) or off (0) SWIR OOB leak correction.	1	1	1	1	1	1		1	1	Step Function LUT		
SWIR_OOB_sending_band	Number of the "sending band" for the SWIR OOB leak correction	1	1	1	1	1	1			1			
SWIR_OOB_sending_detector	Numbers of the "sending detector" for the SWIR OOB leak correction	1	10	1	1	1	10		1	1	Step Function LUT		
T_FPA_ref	Focal Plane temperature reference	1	1	1	1	4	4						
T_inst_ref	Instrument temperature reference	1	1	1	1	1	1		3	1	Step Function LUT		
X_OOB_0	Coefficients of quadratic SWIR band correction formula	4	20	2	2	1	320		1	1	Step Function LUT		
X_OOB_1	Coefficients of quadratic SWIR band correction formula	4	20	2	2	1	320		6	1	Step Function LUT		
X_OOB_2	Coefficients of quadratic SWIR band correction formula	4	20	2	2	1	320		1	1	Step Function LUT		
u1	The uncertainty due to calibrations using on-board calibrators.	1	330	1	1	1	330		13	11	Step Function LUT		
u2	The uncertainty term which is AOI and time independent.	1	330	1	2	7	4620		13	11	Step Function LUT		
u3	The uncertainty due to temperature impact.	1	330	1	2	1	660		13	11	Step Function LUT		
u4	Scene dependent noise to signal ratio.	22	40	4	2	3	21120		13	11	Step Function LUT		
swir_ui_factor	The factor for uncertainty due to cross talk correction for SWIR	4	1	1	1	4			1	1	Step Function LUT		
u2_frames	Frames loaded with RSB u2 uncertainty.	1	1	1	1	7	7		1	1	Step Function LUT		

* 1340 is the total of the products of the Bands, detectors, number of samples, and number of mirror sides for the 250m Bands, the 500m Bands, and the 1KM RSBs. LUTs with this dimension were dimensioned as 22 x 40 x 4 x 2 (B, D, S, M respectively) in LUT HDF files created for L1B Versions 3.1.0 and lower.

QA LUTS V6.1.14.6 (Terra) / V6.1.17.8 (Aqua)

LUT NAME	DESCRIPTION	DIMENSIONS					Total Number of Elements	TIME DEPENDENT LUTS ONLY				
		B	D	S	M	Other		# of Table Pieces	TERRA	AQUA	V6.1.14.6	V6.1.17.8
a1	Pre-launch averages of MODIS linear response term for each emissive detector.	16	10	1	1	1	160					
ALGORITHMPACKAGEACCEPTANCEDATE	Algorithm package date; written to ECS archive metadata.	1	1	1	1	1	1					
ALGORITHMPACKAGEMATURITYCODE	Algorithm package maturity code; written to ECS archive metadata.	1	1	1	1	1	1					
ASSOCIATEDPLATFORMSHORTNAME	Platform (e.g., TERRA or AQUA).	1	1	1	1	1	1					
BB Average Temperature Variance	Pre-launch variance of the average BB temperature.	1	1	1	1	1	1					
Cavity Temperature Variance	Pre-launch variance of the cavity temperature.	1	1	1	1	1	1					
Control options	Miscellaneous code switches	1	1	1	1	2	2					
Detector Quality Flag Values	Integer array identifying noisy, dead and anomalous detectors.	1	490	1	1	8	3920	37	23			Step Function LUT
Detector Quality Flag2 Values	Integer array identifying noisy and dead subframes.	1	180	1	1	8	1440	1	1			Step Function LUT
Instrument Temperature Variance	Pre-launch variance of the instrument temperature.	1	1	1	1	1	1					
LWIR FPA Temperature Variance	Pre-launch variance of the LWIR FPA temperature.	1	1	1	1	1	1					
Mirror Average Temperature Variance	Pre-launch variance of the average mirror side temperature.	1	1	1	1	1	1					
MirrorSide 1 Temperature Variance	Pre-launch variance of the mirror side 1 temperature.	1	1	1	1	1	1					
MirrorSide 2 Temperature Variance	Pre-launch variance of the mirror side 2 temperature.	1	1	1	1	1	1					
mission phase	Mission phase.	1	1	1	1	1	1					
Moon Offset Limits	Defines the limits of the "Keep-out" box relative to center of SVP. (This is not strictly a QA LUT because it is used in processing)	38	1	1	1	4	152					
MWIR FPA Temperature Variance	Pre-launch variance of the MWIR FPA temperature.	1	1	1	1	1	1					
NEdL	Pre-launch noise equivalent difference in radiance for each emissive detector.	16	10	1	1	1	160					
NIR FPA base variance	Pre-launch variance of the NIR FPA temperature	1	1	1	1	1	1					
QA serial number	Version of the science content of the QA LUTs	1	1	1	1	1	1					
Spacecraft_Roll_Threshold_Angle	Upper limit of the absolute deviation from nominal allowed in the spacecraft roll angle	1	1	1	1	1	1					
Spacecraft_Pitch_Threshold_Angle	Upper limit of the absolute deviation from nominal allowed in the spacecraft pitch angle	1	1	1	1	1	1					
Spacecraft_Yaw_Threshold_Angle	Upper limit of the absolute deviation from nominal allowed in the spacecraft yaw angle	1	1	1	1	1	1					
T_BB_Variance	Pre-launch variance of each of the 12 BB temperatures.	1	1	1	1	12	12					
visual FPA base variance	Pre-launch variance of the VIS FPA temperature	1	1	1	1	1	1					

EMISSIVE LUTS V6.1.14.6 (Terra) / V6.1.17.8 (Aqua)

LUT NAME	DESCRIPTION	DIMENSIONS					Terra (T) or Aqua (A) Only	TIME DEPENDENT LUTS ONLY		
		B	D	S	M	Other		# of Table Pieces		
		V6.1.14.6	AQUA	V6.1.17.8	Type of Time Dependent LUT					
A0	Quadratic coefficients for calculating a0	16	10	1	2	3	960	22	5	Step Function LUT
A2	Quadratic coefficients for calculating a2.	16	10	1	2	3	960	22	5	Step Function LUT
Band_21_b1	The value of b1 for each Band 21 detector.	1	10	1	2	1	20	24	13	Step Function LUT
BB_DN_first_frame_to_use	Index of 1st frame for computing BB DN averages	1	1	1	1	1	1			
BB_DN_number_of_frames_to_use	Number of frames for computing BB DN averages	1	1	1	1	1	1			
BB_T_sat_aqua	Saturation temperature for bands 33, 35, and 36	3	1	1	1	1	3	A		
bb_t_sat_default_b1_baseline_aqua	Default b1 baseline for bands 33, 35, and 36 to use if saturated on BB warmup	3	10	1	2	1	60	A	4	Step Function LUT
bb_t_sat_default_b1_c1_aqua	The scale factor for the temperature correction	3	10	1	2	1	60	A	4	Step Function LUT
bb_t_sat_default_b1_Tlwr_baseline_aqua	The baseline temerature for LWIR fpa	1	1	1	1	1	1	A	1	Step Function LUT
BB_T_sat_switch_aqua	Flag to switch to default b1 for bands 33, 35, 36 when BB temperature is above saturation temperature.	1	1	1	1	1	1	A		
BB_Weight	Weight factor used for computing average BB temperature.	1	1	1	1	12	12			
delta_T_bb_beta	The "b" term in the equation for calculating DT_bb.	16	10	1	1	1	160			
delta_T_bb_delta	The "D" term in the equation for calculating DT_bb.	16	10	1	1	1	160			
epsilon_bb	Black-body emissivity.	16	10	1	1	1	160			
epsilon_cav	Effective cavity emissivity.	16	10	1	1	1	160			
L_Max	Top end of radiance dynamic range	16	1	1	1	1	16			
L_Min	Bottom end of radiance dynamic range	16	1	1	1	1	16			
MCST_Version	4-digit ALGORITHM PACKAGE VERSION (e.g. "4.0.5.2_Terra")	1	1	1	1	1	1			
num_overlap_scans_b1	Number of scans in leading and trailing granules for cross-granule averaging of b1	1	1	1	1	1	1			
NWL	Number of values in RSR distribution.	16	10	1	1	1	160			
PC_XT	PC bands cross-talk correction parameters.	5	10	1	1	4	200			
PCX_correction_switch	Switch (0 = OFF, 1 = ON) for the Xtalk correction	1	1	1	1	1	1			
PGE_Version	3-digit PGE version number (e.g. "4.0.5")	1	1	1	1	1	1			
RSR*	Relative spectral responses	16	10	1	1	49	7840	T		
RVS_BB_SV_Frame_No	Frame number for calculating the BB and SV RVS	16	10	1	1	66	10560	A		
RVS_TEBS	Quadratic coefficients for calculating EV RVS for TEBs	16	10	1	2	3	960	3	1	Piecewise Linear LUT
Serial Number of Emissive LUT	Version number of emissive calibration LUTs	1	1	1	1	1	1			
SV_DN_first_frame_to_use	Index of 1st frame for computing SV DN averages	1	1	1	1	1	1			
SV_DN_moon_include_frames	Number of frames after sorting if Moon in SVP	1	1	1	1	1	1			
SV_DN_number_of_frames_to_use	Index of 1st frame for computing SV DN averages	1	1	1	1	1	1			
T_cav_default	Default value of cavity temperature in K	1	1	1	1	1	1			
T_cav_function_flag	Identifies suitable cavity temperature thermistors.	1	1	1	1	4	4			
T_ins_default	Default value of instrument temperature in K	1	1	1	1	1	1			
T_ins_function_flag	Identifies suitable instrument temperature thermistors.	1	1	1	1	4	4			
T_ins_offset	Instrument temperature offset in K.	1	1	1	1	4	4			
T_mir_default	Default value of mirror temperature in K	1	1	1	1	1	1			
T_mir_function_flag	Identifies suitable mirror temperature thermistors.	1	1	1	1	2	2			
TEB_specified_uncertainty	Factor used in computing uncertainty index	16	1	1	1	1	16			
TEB_UL_scaling_factor	Factor used in computing uncertainty index	16	1	1	1	1	16			
WAVELENGTH*	Wavelengths at points of RSRs	16	10	1	1	49	7840	T		
sigma_a0	Coefficients of polynomial fit of uncertainty due to a0.	16	10	1	2	3	960	14	13	Step Function LUT
sigma_a2	Coefficients of polynomial fit of uncertainty due to a2.	16	10	1	2	3	960	14	13	Step Function LUT
sigma_b1_B21	uncertainty due to band 21 b1.	1	10	1	2	1	20	14	12	Step Function LUT
sigma_epsilon_bb	uncertainty due to Black-body emissivity.	16	1	1	1	1	16	1	1	Step Function LUT
sigma_epsilon_cav	uncertainty due to cavity emissivity.	16	1	1	1	1	16	1	1	Step Function LUT
sigma_L_lambda	uncertainty due to wavelength.	16	1	1	1	2	32	1	1	Step Function LUT
sigma_L_Tbb	uncertainty due to Black-body temperature	16	1	1	1	1	16	1	1	Step Function LUT
sigma_L_Tcav	uncertainty due to cavity temperature	16	1	1	1	1	16	1	1	Step Function LUT
sigma_L_Tsm	uncertainty due to scan mirror temperature	16	1	1	1	1	16	1	1	Step Function LUT
sigma_RVS_ev	Coefficients of polynomial fit of uncertainty due to RVS	16	10	1	2	3	960	1	1	Step Function LUT
pcx_ui_factor	The factor for uncertainty due to cross talk correction	5	1	1	1	1	5	1	1	Step Function LUT

* Note that Terra and Aqua have differing numbers of allowed wavelengths for these tables.